

FEATURES

- ※3-state setting
- ※Low profile for space saving


APPLICATION

- ※Remote control
- ※Home automation
- ※Telecommunication


SPECIFICATION

Contact Rating	25mA, 24V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	500V AC/1 minute
Operating Force	1,000gf max.
Travel	0.8mm
Operating Life	2,000 cycles
Operating Temp.	-40°C ~ +85°C
Storage Temp.	-40°C ~ +85°C

HOW TO ORDER






CIRCUIT



PACKAGE

- <Tube>
- TI(I)(R)/TIM(R)-04: 41 pcs
 - TI(I)(R)/TIM(R)-05: 34 pcs
 - TI(I)(R)/TIM(R)-07: 24 pcs
 - TI(I)(R)/TIM(R)-08: 22 pcs
 - TI(I)(R)/TIM(R)-09: 20 pcs
 - TI(I)(R)/TIM(R)-10: 18 pcs
- <Tape & Reel>
- TIM(R): 900 pcs

TI(I)(R)



PART NO.	NO.OF POS.	DIM.A	DIM.B
TI(I)(M)(R)-04	4	11.32	7.62
TI(I)(M)(R)-05	5	13.86	10.16
TI(I)(M)(R)-07	7	18.94	15.24
TI(I)(M)(R)-08	8	21.48	17.78
TI(I)(M)(R)-09	9	24.02	20.32
TI(I)(M)(R)-10	10	26.56	22.86

TIM(R)

